



Woodfast



Model M910 Woodlathe

- Heavy Duty vibration absorbing cast iron construction
- Finely ground bed for reduced friction
- 4 large *QUATRO* design Headstock Bearings
- Heavy Duty steel cabinet stand
- Portable switch controls for operator comfort
- Spindle Lock for easy removal of chucks
- 24 division Index Pin
- Swing over Bed 520mm
- Distance between centres 975mm
- Spindle tapers No 2
- Tailstock Spindle travel 100mm
- **Electronic variable speed** 10 – 3600 rpm
- Spindle Thread 30mm x 3.5 p
- **Powerful fan cooled Motor** 2 hp x 240 volt
- **Micro switch to H/Stock Lid & Cab Door**

Standard Equipment

- 82 mm Face Plate
- 25 mm Spur Drive Centre
- Revolving Cup Centre
- 150 mm Straight Toolrest
- 300 mm Straight Toolrest
- Rear Handwheel Brake
- Face Plate Spanner
- Centre Knock Out Bar
- # Schools Models
- Rear Spindle Guard in Lieu of Rear Handwheel Brake

WOODFAST MACHINERY CO (AUST) Pty Ltd

58 BOTTING STREET,
ALBERT PARK,
SOUTH AUSTRALIA, 5014

TEL 08-8445 2577
FAX 08-8268 2708
e-mail: woodfast@tpg.com.au